

WHAT IS CLAIMED IS:

- 1 1. A method of anchoring a balloon catheter in a patient, comprising the
2 steps of:
3 providing a balloon catheter having a shaft and a balloon mounted to
4 the shaft, the shaft having a distal end and a proximal end, the balloon having
5 an expanded shape and a collapsed shape, the expanded shape being
6 configured to occlude a body passageway in a patient, the balloon including
7 an outer surface having at least two high friction portion and at least two low
8 friction portions, the low friction portion having a lower coefficient of friction
9 than the at least two high friction portions relative to the patient's body
10 passageway, the balloon having at least three radially extending arms when
11 in the collapsed shape, each of the at least two low friction portions being
12 positioned at radially outward extremes of adjacent radially extending arms,
13 the high friction portion being exposed and positioned between the radially
14 outward extremes of the adjacent radially extending arms when the balloon is
15 in the collapsed shape, the high friction portion being everted when the
16 balloon moves from the collapsed shape to the expanded shape;
17 positioning the balloon in the patient's body passageway with the
18 balloon in the collapsed shape so that the radially outward extremes contact
19 the body passageway; and
20 advancing the balloon in the patient to a position to be occluded with
21 the balloon in the collapsed shape;
22 inflating the balloon after the advancing step so that the high friction
23 portion contacts the patient's body passageway for anchoring the balloon in
24 the patient's body passageway.

- 1 2. The method of claim 1, wherein:
2 the positioning step is carried out by inserting the balloon into the
3 patient's arterial system; and
4 the inflating step is carried out with the balloon being positioned in the
5 patient's ascending aorta.

1 3. The method of claim 1, wherein:
2 the providing step is carried out with the balloon catheter having a first
3 lumen and an opening at the distal end fluidly coupled to the first lumen, the
4 opening being configured for delivery of a fluid into a patient,

1 4. The method of claim 3, further comprising the step of:
2 introducing cardioplegic fluid into the patient through the first lumen.

1 5. The method of claim 1, wherein:
2 the providing step is carried out with the balloon catheter having at
3 least three arms extending radially outward from the shaft.

1 6. The method of claim 1, wherein:
2 the providing step is carried out with the high friction portion having a
3 plurality of ribs.

1 7. The method of claim 1, wherein:
2 the providing step is carried out with the shaft having a substantially
3 straight portion and a hooked portion connected to the substantially straight
4 portion.

1 8. A balloon catheter for occluding a body passageway in a patient,
2 comprising:
3 a shaft; and
4 a balloon mounted to the shaft, the balloon having an expanded shape
5 and a collapsed shape, the expanded shape being configured to occlude a
6 body passageway in a patient, the balloon including an outer surface having
7 at least two high friction portions and a low friction portion, the low friction
8 portion having a lower coefficient of friction than the high friction portions
9 relative to the patient's body passageway, the balloon having at least three
10 radially extending arms when in the collapsed shape, each of the at least two

low friction portions being positioned at radially outward extremes of adjacent radially extending arms, the high friction portion being exposed and being positioned between two of the radially outward extremes of the radially extending arms when the balloon is in the collapsed shape, the high friction portion being everted when the balloon moves from the collapsed shape to the expanded shape.

9. The balloon catheter of claim 8, wherein:
the balloon is configured and sized to occlude the patient's ascending aorta.

10. The balloon catheter of claim 8, wherein:
the shaft includes a first lumen and an opening at the distal end fluidly coupled to the first lumen, the opening being configured for delivery of a fluid into a patient.

11. The balloon catheter of claim 8, further comprising:
a source of cardioplegic fluid fluidly coupled to the first lumen.

12. The balloon catheter of claim 8, wherein:
the high friction portion includes a plurality of ribs.

13. The balloon catheter of claim 8, wherein:
the shaft has a substantially straight portion and a hooked portion connected to the substantially straight portion.

14. A method for positioning a balloon in a passageway and occluding the passageway, comprising the steps of:
providing a catheter having a shaft and a balloon mounted thereto, the balloon having a collapsed shape and an expanded shape;
inserting the catheter into a body passageway of a patient with the balloon in the collapsed shape;

7 positioning the catheter in a portion of the body passageway for
8 occluding the portion of the body passageway;
9 inflating the balloon with a fluid;
10 monitoring a rate of pressure increase in the balloon with respect to a
11 fluid volume in the balloon; and
12 adding an amount of fluid after the rate of pressure increase in the
13 balloon exceeds a predetermined threshold.

1 15. The method of claim 14, wherein:
2 the positioning step is carried out by positioning the balloon in the
3 patient's ascending aorta.

1 16. The method of claim 14, wherein:
2 the providing step is carried out with the catheter having a lumen
3 fluidly coupled to the balloon, the catheter also having a pressure sensor and
4 a pressure sensing alarm, the pressure sensing alarm indicating when the rate
5 of pressure increase in the balloon exceeds the predetermined threshold.

1 17. The method of claim 14, wherein:
2 the adding step is carried out with the amount of fluid being a
3 predetermined volume of fluid.

1 18. The method of claim 14, wherein:
2 the adding step is carried out by adding the amount of fluid to increase
3 the pressure in the balloon a predetermined amount.

1 19. A device for pressurizing a balloon catheter, comprising:
2 a catheter having a shaft and a balloon mounted thereto, the balloon
3 having a collapsed shape and an expanded shape, the collapsed shape being
4 configured for advancement within a patient the catheter having a first lumen
5 fluidly coupled to the balloon for inflating the balloon;

6 a fluid source coupled to the first lumen for inflating the balloon;
7 a pressure sensor configured to measure a pressure in an interior of the
8 balloon; and
9 a pressure monitor coupled to the pressure sensor, the pressure
10 monitor determining when a rate of pressure increase in the balloon with
11 respect to an increase in fluid volume in the balloon exceeds a predetermined
12 threshold.

1 20. The device of claim 19, further comprising:
2 means for adding a predetermined amount of fluid after the pressure
3 monitor detects the rate of pressure increase exceeds the predetermined
4 threshold.

1 21. The device of claim 19, further comprising:
2 means for increasing the pressure in the balloon a predetermined
3 amount after the pressure monitor detects the rate of pressure increase
4 exceeds the predetermined threshold.

1 22. A method of anchoring an occluding member in a patient, comprising
2 the steps of:
3 inserting a catheter having an occluding member mounted thereto, the
4 occluding member having a collapsed shape and an expanded shape;
5 positioning the occluding member in a body passageway in the patient;
6 expanding the occluding member to the expanded shape after the
7 positioning step to thereby occlude the body passageway;
8 monitoring a pressure exerted on the occluding member on a distal
9 side and a proximal side of the occluding member; and
10 determining a difference between the pressure on the distal and
11 proximal sides of the occluding member.

1 23. The method of claim 22, further comprising the step of:

2 adjusting a pressure on at least one of the distal and proximal sides of
3 the occluding member.

1 24. The method of claim 22, wherein:
2 the adjusting step is carried out by adjusting a pressure on the distal
3 side of the occluding member.

1 25. The method of claim 22, wherein:
2 the inserting step is carried out with the occluding member being a
3 balloon.

1 26. The method of claim 22, wherein:
2 the inserting step is carried out with the body passageway being an
3 ascending aorta.

1 27. A catheter for occluding an ascending aorta in a patient, comprising:
2 a shaft having a distal end and a proximal end;
3 an occluding member mounted to the shaft, the occluding member
4 having an expanded shape sized to occlude the patient's ascending aorta;
5 a first pressure sensor positioned between the distal end and the
6 occluding member for measuring a pressure on a first side of the occluding
7 member; and
8 a second pressure sensor positioned between the proximal end and the
9 occluding for measuring a pressure on a second side of the occluding
10 member.

1 28. The catheter of claim 27, further comprising:
2 a pressure monitor coupled to the first and second pressure sensors,
3 the pressure monitor determining a pressure difference between the first and
4 second pressure sensors.

1 29. The catheter of claim 28, further comprising:
2 an alarm coupled to the pressure monitor for indicating when a
3 pressure difference sensed by the first and second pressure sensors exceeds a
4 predetermined threshold.

1 30. The catheter of claim 27, wherein:
2 the occluding member is a balloon; and
3 the shaft includes a first lumen, a second lumen and an opening at the
4 distal end of the shaft fluidly coupled to the first lumen, the second lumen
5 being fluidly coupled to the balloon for inflating the balloon.

1 31. The catheter of claim 30, further comprising:
2 means for adjusting the pressure on at least one of the first and second
3 sides of the balloon when a pressure difference sensed by the first and second
4 pressure sensors exceeds a predetermined threshold, the pressure adjusting
5 means reducing the pressure difference to a value below the predetermined
6 threshold.

1 32. The catheter of claim 31, wherein:
2 the pressure adjusting means is coupled to the first lumen for adjusting
3 a fluid pressure exerted by fluid delivered into the ascending aorta through
4 the first lumen.

1 33. A method of anchoring an occluding member in an ascending aorta of
2 a patient, comprising the steps of:
3 inserting a catheter into a patient, the catheter including a shaft having
4 an occluding member at a distal end, the occluding member having a
5 collapsed shape and an expanded shape;
6 positioning the catheter in the patient's ascending aorta;
7 expanding the occluding member to the expanded shape after the
8 positioning step to thereby occlude the ascending aorta; and

9 displacing the shaft of the catheter a first amount after the expanding
10 step so that a predetermined portion of the catheter contacts the patient's
11 aortic lumen for anchoring the occluding member in the ascending aorta.

1 34. The method of claim 33, wherein:
2 the displacing step is carried out by withdrawing an amount of the
3 catheter from the patient so that the predetermined portion of the catheter
4 engages a radially inner portion of the patient's ascending aorta.

1 35. The method of claim 33, further comprising the step of:
2 displacing the catheter a second amount in a direction opposite to the
3 first amount so that a second predetermined portion of the shaft engages a
4 radially outer wall of the patient's ascending aorta.

1 36. The method of claim 33, further comprising the step of:
2 inserting the shaft through a delivery cannula, the delivery cannula
3 having a shaft engaging mechanism and a shaft displacing mechanism;
4 the displacing step being performed with the shaft displacing
5 mechanism of the delivery cannula.

1 37. A catheter having an expandable member for occluding an ascending
2 aorta in a patient, comprising:
3 a shaft having a longitudinal axis, a distal end, a proximal end, a first
4 lumen and an opening at the distal end in fluid communication with the
5 opening, the opening being configured for delivery of a fluid into the
6 patient's ascending aorta;

7 an expandable member mounted near the distal end of the shaft, the
8 expandable member having an expanded shape and a collapsed shape, the
9 expanded shape being configured to occlude the patient's ascending aorta;
10 and

11 a delivery cannula, the shaft being movably coupled to the delivery
12 cannula for movement in a direction parallel to the longitudinal axis in an
13 inward direction and an outward direction;

14 the shaft having a first portion configured to contact the radially inner
15 wall of the aortic lumen when the shaft is slidably displaced in the outward
16 direction.

1 38. The catheter of claim 37, further comprising:

2 a shaft displacing mechanism coupled to the delivery cannula, the shaft
3 displacing mechanism being configured to displace the shaft a predetermined
4 amount in the outward direction so that the first portion engages the radially
5 inner wall of the aortic lumen.

1 39. The catheter of claim 37, wherein:

2 the shaft includes a second portion configured to contact a radially
3 outer wall of the aortic lumen when the shaft is slidably displaced in the
4 inward direction.

1 40. The catheter of claim 39, wherein:

2 the shaft includes a third portion configured to contact the radially
3 outer wall of the aortic lumen when the shaft is slidably displaced in the
4 inward direction, the second portion being positioned between the first and
5 second portions.

1 41. The catheter of claim 37, wherein:

2 the delivery cannula includes a lumen for introducing a fluid into the
3 patient.

1 42. The catheter of claim 37, wherein:

2 the shaft includes a first bend and a second bend, the first portion
3 being positioned between the first and second bends.

1 43. A method of anchoring an occluding member in a patient comprising
2 the steps of:
3 inserting a catheter into a patient, the catheter having an occluding
4 member mounted thereto;
5 positioning the occluding member at a desired location;
6 expanding the occluding member to occlude the desired location; and
7 clamping a portion of the passageway adjacent the desired location to
8 prevent migration of the occluding member.

1 44. The method of claim 43, wherein:
2 the inserting step is carried out with the occluding member being a
3 balloon.

1 45. The method of claim 43, wherein:
2 the clamping step is carried out by clamping the body passageway
3 around the balloon thereby trapping the balloon.

1 46. The method of claim 43, wherein:
2 the inserting step is carried out with the balloon having an indentation;
3 and
4 the clamping step is carried out with the clamp being positioned
5 around the indentation.

1 47. A method of anchoring an occluding member in a patient's ascending
2 aorta comprising the steps of:
3 inserting an occluding member in the ascending aorta between the
4 coronary ostia and the brachiocephalic artery;
5 expanding the occluding member in the patient after the inserting step;
6 positioning an anchor in the brachiocephalic artery, the anchor having
7 a proximal end extending into the aorta, the anchor preventing migration of
8 the occluding member beyond the brachiocephalic artery.

1 48. The method of claim 47, wherein:
2 the positioning step is carried out with the anchor being a perfusion
3 catheter configured to deliver oxygenated blood to the brachiocephalic artery.

1 49. The method of claim 47, wherein:
2 the anchor is separate from the catheter.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000